

Corzo

User manual

Table of Contents

Intended Use	3
Warranty	3
Safety and Warning Notes	4
Transportation	5
Overview of the Corzo X Country	6
Technical Specifications	7
Configuration	7
Box Contents	7
Unboxing the Corzo X Country	7
Assembling the Corzo X Country	8
Hex Key	8
Opening the Stroller	8
Footrest Installation	8
Adjustment	9
1. Seat Depth	9
2. Backrest and Handle Height Adjustment	9
3. Brakes	9
4. Five-point Belt	9
5. Seat Reinforcement	10
6. Backrest Angle Adjustment	10
Daily Usage	10
Opening the Stroller	10
Folding the Stroller	11
Getting into the Stroller	11
Getting out of the Stroller	11
Negotiating Stairs	11
Negotiating Curb or Single Steps	12
Accessories	13
Canopy Comfort (010-141)	13
Abductor Block – 010-132	13
Headrest Adjustable (Pair) – 010-131	14
Headwings Basic (Head laterals) – 010-166	14

Thigh Fixation – 010-169.....	15
Work Board 010-144.....	15
Feet Fixation – 010-134.....	16
Chest Immobilisation Belt – 010-168.....	16
2-Point Safety Belt – 010-137	17
H-Style Harness – 010-178	17
Winter Footmuff – 010-139.....	18
Basket – Textile – 010-143.....	18
Armrest Foldable (Pair) – 010-147.....	19
Comfort Seat Cover – 010-171.....	19
Rain Cover – 010-142	20
Summer Footmuff – 010-138	20
Immobilisation Vest – 010-136.....	21
Comfort Side Protection – 010-133.....	22
MAINTENANCE OF ACCESSORIES	22
Cleaning Instructions	22
Armrests	22
Maintenance	23

IMPORTANT:

The information in this document is subject to change without notice. For more information, please contact our Customer Service at:

Toll free: 1-888-752-8818

Phone: 1-450-759-9449

Fax: 1-450-752-1644

Email: info@synetikergocare.com

Website: www.synetikergocare.com

Business Hours: 8 am to 4 pm Eastern Time

Only use parts and accessories supplied by Synetik ErgoCare. Any substitution of parts with those of another company will result in the loss of warranty and may cause damage.

Read this manual carefully before using the stroller for the first time and keep it for future reference. The safety of a child could be compromised if you do not follow the instructions and safety notices mentioned in the User Guide.

In case of apparent defects, which limit the safe use of the product (for example, the chassis is damaged, there are cracks or a visible defect), it is imperative to immediately stop using the product and contact your distributor or local repair centre. Synetik ErgoCare assumes no liability for damages and accidents caused by improper use of its products.

Intended Use

The Corzo X-Country stroller comes in 4 sizes (30, 34, 38 and 42). This stroller is produced from lightweight alloy. It is equipped with an optimized folding system and is fully adjustable. Indeed, the seat depth, the backrest height, the upholstery tension and the footrest height are adjustable. The stroller also comes with solid steel wheels for a stable ride. You will find all the details in the assembly section.

Warranty

1. A 24-month warranty is applicable on this product from the date of sale. The warranty applies to material and manufacturing defects.
2. The warranty is applicable at the location where the product was purchased, or in an authorized service repair shop.
3. A properly completed Certificate of Warranty and a copy of the proof of purchase must be presented when applying for the warranty. Do not remove the identification label. It must be legible and undamaged throughout the entire warranty period.
5. The product must be used entirely for the purpose for which it is designed for, the user must follow the directions mentioned in the Instructions for Use. The manufacturer/distributor is not responsible for defects caused by any handling that is contrary to the instructions for use.
6. The product must be used, treated, maintained and stored properly according to directions mentioned in the instructions for use.
7. Warranty proceedings can be initiated, if the product under claim has been returned completely in the original package, carefully packed and protected against damage. The owner is obliged to ensure the product under claim is properly cleaned, hygienically flawless as per general hygienic principles. The owner cannot ask the seller to do basic maintenance or cleaning of the product throughout the claim proceedings.
8. All defects must be claimed immediately.
9. The warranty is forfeited if the defects were caused by overloading, accident, violence or inappropriate tampering or mishandling of the product.

If you have any questions or comments, you can contact our Customer Service.

IDENTIFICATION SHEET

Identification tag / Product type (write up):

Final inspection:

Name:

Signature:



Safety and Warning Notes

ATTENTION! Read this manual carefully before first using the stroller, and keep it for further reference. The safety of a child might be in jeopardy if the instructions and safety information listed in the User Guide are not followed.

Safety points to consider when using the Corzo X Country Stroller.

- BAGS ATTACHED TO THE HANDLE AFFECT THE STABILITY OF THE STROLLER
- NEVER LEAVE YOUR CHILD UNATTENDED
- MAXIMUM LOAD CAPACITY OF THE STROLLER:
 - 45 kg (size 30)
 - 55kg (size 34)
 - 75kg (sizes 38 and 42)
- **WARNING !** Keep fingers and covers out of any moving parts when using the stroller.
- **WARNING !** Never leave your child unattended! Even if the belts and brakes are in use.
- **WARNING !** Check before use that all locking devices are properly secured and all safety equipment is properly used.
- **WARNING !** The seat unit is not suitable for a child younger than 6 months.
- **WARNING !** This product must not be used while jogging or rollerblading.
- The attendant must be familiar with the instructions of this manual.
- Professional medical advice regarding the suitability of this product must be sought before use.
- Always make sure, before heading out, that the child is comfortable, and that clothes and blankets, etc., are tucked in, so they do not get caught in the wheels.
- Ensure that child is clear of moving parts before making adjustments, to avoid any injury.
- When angle positioning and adjusting the seat and backrest act accordingly to avoid sudden uncontrolled movements.
- Do not allow the child to climb unassisted into and out of the stroller.

- Always apply the parking brakes when putting the child in and taking them out of the stroller.
- Make sure that the belts and other securing accessories, safety bar and other equipment are fitted and adjusted correctly.
- Do not stand on the footrest.
- The brakes must be engaged at all times when the stroller is not moving.
- Getting over the curb: Practice first using an empty stroller.
- The stroller is not designed to be used in the stairs.
- The attendant must take precautions against fire risk. In buildings, check the location of fire exits and ensure all procedures are understood.
- Do not let children play with or hang onto the stroller.
- Do not overload the stroller. Overloading the chassis, seat, bag or basket causes a reduction in stability of the stroller.
- Pay full attention, when handling the stroller, so not to injure the child or yourself.
- If it is possible, always use ramps or elevators to avoid any access restrictions.
- If possible, two people should lift the stroller.
- When you use the stroller on the road, follow the road traffic regulations.
- Do not use the stroller for any purpose other than what it is designed for.
- The stroller is designed to carry only one child.
- Do not use anything other than original PATRON accessories designed for this product.
- When the stroller is folded and unfolded, the User Guide must be followed carefully, to avoid any damage to the construction that may affect product stability.
- In case of apparent defects, which limits the product's safe use (e.g. damaged chassis, part comes off or other visible defects, cracks, etc.) it is necessary to stop using the product immediately and contact your local official distributor or service centre.
- Synetik ErgoCare does not bear any responsibility for the damages and accidents caused by inappropriate use of this product.


Transportation

The Corzo X Country stroller-style wheelchair has successfully passed impact tests. The seat meets the ISO 7176-19. The tests were carried out in all possible configurations of the product.

To be compliant, the wheelchair must have the transit option which includes 4 tie-downs.

Overview of the Corzo X Country

SCHEMA



SCHEMA DESCRIPTION

1. Handle	15. Seat safety pin
2. Handle adjusting lever	16. Footrest adjusting lever
3. Handle adjusting safety pin	17. Front wheel
4. Backrest frame	18. Calf rest
5. Backrest	19. Footrest safety
6. Cross frame	20. Footrest
7. Safety belt	21. Arrestment device spring
8. Seat frame	22. Seat
9. Parking brake	23. Extension seat adjustment
10. Rear wheel	24. Side frame
11. Back safety crossbar	25. Side frame cover
12. Transport safety-catch	26. Backrest height extension
13. Seat reinforcement	27. Frame
14. Seat crossbar	28. Seat clip reinforcement

Technical Specifications

Measurements	CRX 30	CRX 34	CRX 38	CRX 42
Backrest Height	21.7–25.6	22.8–27.2	26–33.6	26–36.6
Seat Depth	11–13.4	11.4–13.8	12.6–15.3	13-15.7
Seat Width	11.8	13.4	15	16.5
Seat to Footrest	12.2–17.3	12.6–18.1	11.4–17.7	13.8–20.5
Backrest Angle (°)	90, 89	94, 91	90, 88	94, 92
Seat Angle (°)	20	25	25	21
Total Length	38.6	40.6	45.3	45.3
Total width	20.9	22.8	24.8	25.6
Total Height/with Handle	39.8/44.1	38.6/42.5	40.2/46.5	47.6/52.0
Total Weight	12.5 kg	13 kg	14 kg	14.7
Maximum Load	45 kg	55 kg	75 kg	75 kg
Folded Stroller Length	12.6	12.6	13.78	14.6
Folded Stroller Width	46.1	46.1	47.2	49.6
Folded Stroller Height	13.8	14.6	15	13.8

*inches

Configuration

Box Contents

Upon delivery, you will receive one (1) box containing the stroller and the accessories ordered. The only tool required for assembly, a hex key, is found in a small pocket on the bottom left corner of the back of the backrest. Always put the key back in place.

Items list:

- Stroller-style fixed tilt wheelchair
- Hex Key
- Accessories
- 2 Footrests
- 5-point Belt

Unboxing the Corzo X Country

- 1- Remove the contents of the boxes and place on a flat surface.
- 2- Make sure that the material corresponds to what you ordered and that no damage was caused during transportation.
- 3- Follow the instructions in the following section (Assembling the Corzo X Country)

Assembling the Corzo X Country

The instructions in the User Guide will guide you through the assembly process of the positioning seat. However, it is recommended that the initial adjustment for the user be done in the presence of a Synetik ErgoCare representative.

NOTE! The numbers in parenthesis refers to the schema presented on page 6.

Hex Key

Only one Hex key is needed to assemble and adjust the Corzo X Country Stroller. It is located in a pocket on the bottom left corner of the back of the backrest.

Opening the Stroller

To complete the assembly, you need to;

1. Stand stroller on its wheels
2. Unlock the transport safety latch (12)
3. Grasp one handle (1) and push down on the opposite seat tube (22), press down firmly on seat tubes to ensure the stroller is completely open.
4. Use foot to lock the rear brace into a straight position
5. Wrap the armrest padding around the armrests (25)
6. Mount the footrest onto the stroller. (see footrest installation section)
7. Lock the seat brace—Sizes 38–42 only

Footrest Installation

Install;

- 1- Loosen the footrest adjusting lever (16)
- 2- Insert the footrest tube into the footrest opening until it reaches the safety pin (21)
- 3- Pull the safety pin while pushing on the footrest
- 4- Release the safety pin and pull gently on the footrest until it stops at the lowest position
- 5- Tighten the adjusting lever
- 6- Repeat for the second footrest.

Height Adjustment;

- 1- Loosen the adjusting lever (16)
- 2- Pull the safety pin towards you (21) and adjust the footrest into desired position
- 3- Release the safety pin and tighten the adjusting lever to secure the footrest in position
- 4- Repeat for the second footrest.

Uninstall;

- 1- Loosen the adjusting lever (16)
- 2- Pull the safety pin towards you (21) and pull the footrest tube out of the opening
- 3- Release the safety pin and retighten the adjusting lever
- 4- Repeat for the second footrest.

Adjustment

Before placing the child in the stroller, adjust the height of the backrest, the depth of the seat and install the desired accessories.

** Use the hex key to handle the screws

1. Seat Depth

The seat should support the length of the thighs. To change the seat depth, you need to;

- 1.1 Undo the Velcro panel connecting the seat and backrest.
- 1.2 Partially fold the stroller to relieve fabric tension.
- 1.3 Hold the end of the seat tube firmly, press the safety pin (15) and move the seat tube (23) until the spring button relocates into the desired hole.
- 1.4 Repeat for other side of seat.
- 1.5 Fully open the stroller and fasten the Velcro panel connecting the seat and backrest.

2. Backrest and Handle Height Adjustment

- 2.1 Undo the Velcro straps on the backrest extension (26) – Size 38 and 42 only
- 2.2 Partially fold the stroller to relieve fabric tension.
- 2.3 Position the push handle perpendicular to the seat back
- 2.4 Firmly grip the push handle (1), loosen the handle adjusting knob (2) by using the hex key in the pocket located at the bottom left corner of the backrest
- 2.5 Pull the push handle adjusting safety pin (3)
- 2.6 Move the push handle until it relocates into desired position, release push handle adjusting safety pin until it relocates into the desired hole
- 2.7 Tighten the push handle adjusting knob
- 2.8 Repeat for the other handle and fully open the stroller. (Fasten all Velcro straps on the backrest extension -Size 38 and 42 only)

3. Brakes

To engage the brake, press brake lever pad on both sides fully to the end position. To disengage the parking brake, lift both brake lever pads.

4. Five-point Belt

- 4.1 Release all plastic quick fasteners (fork type).
- 4.2 Place the child into the stroller and adjust the belt to desired lengths.
- 4.3 Choose the hole in backrest (5) to adjust the proper position of the shoulder straps. The hole should be level with or higher than the top of the shoulders.

- 4.4 The shoulder straps must be mounted onto the backrest and backrest extension at once – Size 38 and 42 only

5. Seat Reinforcement

You can increase or decrease the seat tension by adjusting the seat frame:

- 5.1 Extend the seat reinforcement straps to reduce tension.
- 5.2 Shorten the seat reinforcement straps to increase tension.
- 5.3 Never change the width of the seat by adjusting the seat tension.

6. Backrest Angle Adjustment

- 6.1 Loosen and remove the two screws that are located on each side of the seat frame (8) by using 2 wrenches (see image)
- 6.2 Gently move the seat up or down so that the screws can run in the other hole (see image)
- 6.3 Insure that the seat is parallel to the ground and tighten the two screws by using 2 wrenches



Daily Usage

Synetik ErgoCare recommends performing a daily inspection before seating a child in the Corzo X Country Stroller.

Opening the Stroller

1. Stand stroller on its wheels
2. Unlock the transport safety latch (12)
3. Grasp one handle (1) and push down on the opposite seat tube (22), press down firmly on seat tubes to ensure the stroller is completely open
4. Use foot to lock the rear brace into a straight position
5. Wrap the armrest padding around the armrests (25)
6. Mount the footrest onto the stroller. (see footrest installation section)
7. Lock the seat brace—Sizes 38–42 only

Folding the Stroller

1. Flip up the footrests on each side. It is no necessary to remove the footrests
2. Remove the armrest padding by undoing the Velcro section and metal snaps (25)
3. Use your foot to release the rear safety bar by pushing up on the centre of the brace
4. Firmly grip one push handle and pull up the seat tube with other hand
5. Make sure that the backrest is leaning toward the stroller seat to prevent damage to the spacer folding mechanism
6. Lock the transport safety latch (12)

Getting into the Stroller

1. Ensure the brakes (9) are on
2. To make access easier, the footrests can be flipped up on each side
3. If possible, place the back of the stroller against a wall or immovable object (Another helper can hold the stroller steady)
4. Place the child carefully into the stroller
5. Fasten the safety belt and flip the footrests back down carefully
6. The child must always feel comfortable.

Getting out of the Stroller

1. Ensure the brakes are on
2. If possible, place the back of the stroller against a wall or immovable object (Another helper can hold the stroller steady)
3. Unfasten the safety belt and lift the child out carefully.

Negotiating Stairs

To facilitate travel;

1. Where possible stairs should be avoided if there is no alternative to stairs.
2. If not, ensure at least one helper is available to provide assistance.
3. Do not attempt to take the stroller up or down a flight of stairs unless you and your helper are sure you have control of the stroller and can support the weight of its occupant.
4. Do not lift the stroller using the footrests

If no alternative is possible, follow these steps:

Going down steps;

1. Position the stroller squarely with the front wheels on the top step.
2. Tilt the handle backward and push the stroller forward until the rear wheels are at the top step.
3. The helper stands in front, steadies and lowers the stroller by firmly holding on to the front frame.
4. Support the weight and lower the rear wheels down the stairs.

5. Continue step by step to the bottom. (see Pic.1)



Going up steps;

1. Position the stroller squarely with the rear wheels against the bottom step.
2. Tilt the stroller backward and raise toward the next step.
3. The helper stands in front, steadies and lifts the stroller by firmly holding on to the front frame.
4. Continue step by step to the top. (see Pic.2)



Negotiating Curb or Single Steps

Down;

1. Position the rear wheels at the edge of the curb.
2. Hold the handles firmly and tip the stroller slightly backwards.
3. Balance on the rear wheels, lower the stroller down off the curb on its rear wheels.
4. Never tip the stroller forward at a curb.

Up;

1. Position the rear wheels at the curb.
2. With a firm grip on the handles, tilt the stroller backwards and place the rear wheels on top of the curb.
3. Position the front wheels at the curb bottom and lift to the upper level.

Caution

1. During this operation, the attendant and helper must be well positioned and have a secure grip on the stroller.

2. The attendants' hands must be inside the handle straps at all time.
3. Rest at regular intervals.
4. Do not lift the stroller by the footrests.

Accessories

Canopy Comfort (010-141)

Install –

- 1- Insert canopy brackets into both side attachments located on the backrest frame (see Fig. 1 and 2),
- 2- The canopy adjusts by pushing forward or pulling back on the canopy frame.

Remove –

- 1- Squeeze on the canopy fitting releases and pull the canopy section out of the hood attachments. (see Fig. 3)



Fig 1.




Fig.2



Fig.3

Abductor Block – 010-132

Put the buckle, which is sewn onto the bottom part of the block, through one of two holes on the seat, and secure the block using Velcro. (Place zipper outwards).



Headrest Adjustable (Pair) – 010-131

Different positions are possible with the headrest. Adjust the headrest height by changing the shorter Velcro straps (underneath) between the different backrest holes. Before securing the headrest onto the backrest, set the headrest width.

Headrest Width -. Unfasten the metal snaps on the back of the cushion and pull the headrest cushion off of the side straps. Rotate the cushion 180 degrees and insert the side belts again. Then refasten the cushions using the metal snaps on the back of the cushion.

Highest Position - The shorter Velcro straps (underneath) go through the top holes of the backrest and the longer Velcro straps (at top) flip over the edge of the backrest. The belts on back of the backrest are secured by metal snaps.

Lowest Position -The shorter Velcro straps (underneath) go through the appropriate holes at the base of the backrest and the longer Velcro straps (at top) go through of backrest base over top of the shorter straps. The straps on the backrest are then secured with metal snaps.



Headwings Basic (Head laterals) – 010-166

Different positions are possible with the headwings. Adjust the height of the headwings by threading the shorter Velcro straps (underneath) between the different backrest holes.

- 1- Highest Position - The shorter Velcro straps (underneath) go through the top holes of the backrest and the longer Velcro straps (at top) flip over the edge of the backrest. The belts on back of the backrest are secured by metal snaps.
- 2- Lowest Position -The shorter Velcro straps (underneath) go through the appropriate holes at the base of the backrest and the longer Velcro straps (at top) go through of backrest base over top of the shorter straps. The straps on the backrest are secured with metal snaps.



Thigh Fixation – 010-169

Mounting –

- 1- Attach the thigh support to the seat using the Velcro straps.
- 2- Place the thigh support on the front part of the stroller seat and Velcro the straps underneath the seat
- 3- Secure the child's thighs in place using the Velcro straps, which you thread through the metal clips. Make sure that the child's legs are sufficiently secured but not too tightly. The user must always feel comfortable.



Work Board 010-144

- 1- Gently install the work board on the laps of the child
- 2- Wrap the straps around the seat tubes
- 3- Adjust the tension with the Velcro straps. The user must always feel comfortable.



Feet Fixation – 010-134

Mounting –

- 1- Attach the belts to the footrest with Velcro straps.
- 2- Thread the straps through the footrest holes and on the underside of the footrest.
- 3- Secure the child's ankles by threading the straps through the metal clips and securing them with Velcro. Make sure the child's ankles are sufficiently secured, but not too tightly. The user must always feel comfortable.



Chest Immobilisation Belt – 010-168


- 1- Unfasten the 5-point belt, seat the child in the stroller to determine appropriate height for the position of the trunk support.
- 2- Take the child out of the stroller.
- 3- Position the trunk support at the appropriate height and secure it using the lateral belts with the side-release interlocking buckles located on the back of backrest. The 5-point belt must be inside the trunk support.
- 4- Unfasten the Velcro section on the front of the trunk support, seat the child in the stroller and fasten the 5-point safety belt. Then fasten the trunk support using the Velcro attachment to provide the support, ensuring the child is secure yet comfortably seated.



2-Point Safety Belt – 010-137

Fitting –

- 1- Thread the straps through the anchor points on each side of the backrest and secure them with the plastic buckle.




Adjusting –

- 1- Seat the child in the stroller, adjust the length of the straps with the plastic buckles at the end of each strap or by pulling on one of the D-Ring on each side of the buckle
- 2- Fasten the lock. The child must always feel comfortable.

H-Style Harness – 010-178

Fitting –

- 2- Remove the plastic buckles from the upper straps of the harness and pass these straps through the holes in the backrest at the appropriate height for the children shoulders.
- 3- Thread the straps through the plastic buckles and secure them.
- 4- Thread the lower straps through the anchor points on each side of the backrest and secure them with the plastic buckle.



Adjusting –

- 3- Unfasten the front plastic clip and open the H-style harness.
- 4- Seat the child in the stroller, adjust the length of the straps with the plastic buckles at the end of each strap and fasten the locks. The child must always feel comfortable.



Winter Footmuff – 010-139

- 1- Place the footmuff over the seat.
- 2- Attach the upper Velcro straps to the rear part of the backrest.
- 3- Attach the lower straps of the footmuff to the footrest using the zipper.



Basket – Textile – 010-143

The maximum load of the fabric basket is 3 kg.

- 1- Secure the higher part of the basket by wrapping the two straps around the front side frames and fastening the metal snaps (see image)
- 2- Secure the lower part of basket by wrapping the two straps around the rear side frames and fastening the metal snaps (see image)



Armrest Foldable (Pair) – 010-147

Installation-

- 1- Remove the left armrest cover cushion.
- 2- Insert the screw through the inner side of the tube and the hole of the armrest cover (25)
- 3- Secure using a washer and a nut. Cover them using the plastic cap.
- 4- Slide armrest cover back on.
- 5- Repeat for the right armrest cover.



Comfort Seat Cover – 010-171

- 1- Unfasten the shoulder straps of the 5-point belt. Remove the straps from the holes in backrest.
- 2- Unfasten the side straps of the 5-point belt.
- 3- Use your foot to unlock the rear safety bar by pushing the centre of the brace upward.
- 4- Fold the stroller slightly.
- 5- Place the cover on the seat.
- 6- Fasten the Velcro straps on the cover to the top rear of the backrest.
- 7- Find the appropriate position for the middle fastening strap - it must align with the groove between backrest and seat.
- 8- Fasten the backrest middle fastening straps to the seat cover.
- 9- Cut a slot in the leatherette strap according to the position of the seat section of 5-point belt. Thread the seat section of the 5-point belt through the hole in the cover.
- 10- Flip the seat cover over the front edge of the seat and secure the seat straps in the space between the cover and the seat.

- 11- Refer to the image if you have a stroller Size 38 and/or 42 and you are using the backrest height extension.
- 12- Finally, thread the shoulder straps of 5-point belt through the holes of the padded seat cover and through leatherette holes in the backrest.



Rain Cover – 010-142

The rain cover should be pulled over the stroller, so the canopy and the footrest are both covered. Store when clean and dry.



Summer Footmuff – 010-138


- 1- Mount the upper section of the footmuff to the tubing by stretching the fabric to the back side, using plastic sleeves.
- 2- Fasten the two straps on each side of the footmuff to the chassis tubing using the Velcro section.



Immobilisation Vest – 010-136

Fitting –

- 1- Remove the plastic buckles from the upper straps of the vest and thread the straps through the holes of the backrest at the appropriate height for the children shoulders.
- 2- Insert the straps through the plastic buckles and secure them.
- 3- Wrap the middle straps around the backrest and secure them with rear buckles.
- 4- Insert the lower straps through anchor points on each side of the backrest and secure them with the plastic buckle.



Adjusting –

- 1- Unzip the chest support or if necessary, unfasten the front release buckles.
- 2- Seat the child in the stroller.
- 3- Adjust the length of all straps and fasten the buckles. The child must always feel comfortable.



Comfort Side Protection – 010-133

- 1- Attach to the backrest of the stroller using the Velcro band
- 2- Wrap the lower part around the armrest structure and secure with Velcro straps



MAINTENANCE OF ACCESSORIES

- If the accessories are damaged or in need of repair, only an approved repair centre is permitted for this service. Synetik ErgoCare is also available for product information.
- Only PATRON replacement parts should be used on these accessories.
- Ensure you are familiar with using the accessories.
- All accessories can be handwashed.
- Never clean with ammonia-based, bleach-based or alcohol-based cleaners.
- After exposure to damp conditions, let dry in warm environment.
- Store the accessories in a dry and safe place.
- PATRON reserves the right to make design changes to any of their products as part of their continuous development programme.

Cleaning Instructions

The seat, seat reinforcement, backrest and backrest extension are not detachable. You can clean them using warm water and a mild detergent.

Armrests

1. Undo the Velcro and button to remove the armrest upholstery.
2. Wash by hand in hot water (Max. 40 °C) using a mild detergent.

Maintenance

Synetik ErgoCare recommends that a daily visual inspection of equipment be performed by a therapist, parent or caregiver to ensure the safe use of the product.

- Your Stroller has been designed to a high standard and with correct use and maintenance will provide many years of trouble-free service.
- Regularly inspect locking devices, catches, footrest, joint strapping to ensure they are secure and in full working order.
- Brakes, wheels, tires are subject to wear and should be replaced if necessary, by an authorized repair person approved by the stroller supplier.
- We recommend that the stroller be checked by authorized repair person every 12 months.
- We recommend that after 24 months, visit an authorized service department
- If the stroller is damaged or in need of repair, the authorized repair person will be able to advise on what is required.
- Alternatively, Synetik ErgoCare Customer Service Department is available for product information.
- Only PATRON Bohemia a.s. replacement parts should be used on this stroller.
- Should parts of your stroller become stiff or difficult to operate (no later than every 6 months), ensure that dirt is not the cause, apply a light application of a spray lubricant e.g. WD 40 (do not use oil or grease). Ensure that the lubricant penetrates between the components but do not overspray as this may encourage the accumulation of dirt. Wipe off any excess spray. Regular lubrication of moving parts will extend the life of your stroller and make opening and folding the device easier.
- Make sure that you are familiar with the operation of the stroller. It should always open and fold easily. If it does not, do not force it - stop and read the instructions.
- Wheels, plastic and metal parts may be wiped clean with warm water and mild detergent.
- The seat fabric can be washed by hand (Max. 30 °C).
- Never clean with abrasive, ammonia-based, bleach-based or spirit-type cleaners.
- After exposure to damp conditions, dry off with a soft cloth and leave fully open in warm environment.
- Store your stroller in a safe, dry place.
- Check and tighten the screw connections regularly.
- If there are used control cables (brakes, telescopes, tilt), check it regularly and, if necessary, oil them.
- Synetik ErgoCare reserves the right to make design changes to any of their products without prior notice as a part of their continuous development program.